




All dimensions are in mm; tolerances according to ISO 2768 m-H

Description

These fiber optic jumper cable assemblies connect remote radio heads in telecommunication applications. Side A is equipped with an LC-Connector. The divider is overmolded and is especially designed for solid straight connections. Side B is equipped with an LCS connector, the fan-out on the LCS connector is not outdoor rated.

The assembly can be used indoor and outdoor. The cable is UV protected and riser rated.

Available Variants

Type	Length (mm)	Weight (g) / pce
L98B-A0733-3000	3000	tbd.
L98B-A0733-5000	5000	tbd.
L98B-A0733-10000	10000	tbd.
L98B-A0733-15000	15000	tbd.

Length (m)	Tolerances (mm)
$L \leq 10$	+100/-50
$10 < L \leq 30$	+200/-100
$L > 30$	+/-1%

Cable assemblies in additional length variants are available.

Parts

Connector top	1x LC-Simplex, single mode
Connector bottom	1x LC-Simplex, single mode
Cable	UL-approval UL 1651 OFNR (UL1666) Flame retardant acc. to IEC 60332-1, black

Optical data

Cable	2 Fibers 9/125 µm single mode optical fiber according to ITU-T
Fiber	G657A1 and G652D
Cable attenuation	≤ 0.35 dB / km $\lambda = 1310$ nm ≤ 0.25 dB / km $\lambda = 1550$ nm

Technical Data Sheet

Rosenberger

FTTA Fiber Cable Assembly
LCS-HM – 9µG657 – LCS

FB-L98B-A0733-XXX

Connectors
Insertion loss

LC Connectors

Typ. 0.10 dB

Max. 0.30 dB

Return loss


Typ. 50 dB (UPC)

Bending radius min. at boot

60 mm

Bending radius min. fan-out

30 mm



Mechanical data

Cable diameter, jacket

7 mm

Minimum bending radius cable

Installation

105 mm

Operation

70 mm

Max. tensile strength cable

Installation

1200 N

Permanent

600 N

Max. tensile strength fan-out

Installation/Permanent

100N

Crush resistance cable, (short term)

2200 N / dm

Crush resistance cable, (long term)

800 N / dm

Impact resistance acc. To IEC 60794-1-2, method E4

3 Impacts

1.5 Nm

Environmental data

Temperature range operation

-40°C to +85°C

Temperature range storage

-55°C to +85°C

Temperature range installation

-20°C to +60°C

RoHS

Compliant

UV resistance

Acc. to DIN53387

Good resistance to oil, petrol and leach

Packing

Standard:

Length < 20 m

3 pce in box

Length ≥ 20 m

1 pce in box

Length ≥ 175 m

1 pce on cardboard drum

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
A. Burggraf	29/11/18	S.Wiener	29/11/18	100	18-0004	A.Burggraf	29/11/18

Corporate Headquarters
Rosenberger Hochfrequenztechnik GmbH & Co. KG
P.O. Box 1260 D-84526 Tittmoning Germany
Tel. +49 8684 18-0

Rosenberger Site Solutions, LLC
P.O. Box 4268, Lake Charles, LA 70606
Ph.337.598.5250 Fax: 337.598.5290 rlss@rlss.us
www.RosenbergerOnline.us

Page
2 of 2