Technical Data Sheet 1- 5/8" Hanger Grommet		Rosenberger Site Solutions
		CX934-48207
mm round holes. When installed properly, this printstallation in High Risk PIM Zo	mmet with four 15.7 mm and four 7 roduct meets the requirements for ones. For use in High Risk PIM Zones, onjunction with other High Risk PIM	
All dimensions are in mm.		Scale 1:1.5
General Specifications		Note
Type: Cables per Grommet: Dimmensions: Height: Hole Shape:	Multi-hole Grommet 8 (eight) 56.00 mm [2.204 in] Round	Installation of this product should only be performed trained, qualified and experienced personnel. Installa instructions for this product should be read thorough before installation is performed. The manufacturer an supplier of this product disclaims any liability or responsibility for the results of improper or unsafe installation practice.
Cable Hole size: Material Specifications	15.70 mm & 7.00 mm [0.618 in & 0.275 in]	
Material Type:	Rubber	
	Rubber ASTM-1200 and ASE I2000 Unaffected by ozone, sunlight, aging or hot and cold weather. RoHS Compliant	
Standards:	ASTM-1200 and ASE I2000 Unaffected by ozone, sunlight, aging or hot and cold weather.	
Standards: Packaging	ASTM-1200 and ASE I2000 Unaffected by ozone, sunlight, aging or hot and cold weather.	
Material Type: Standards: Packaging Packaging quantity: Weight Per Package	ASTM-1200 and ASE I2000 Unaffected by ozone, sunlight, aging or hot and cold weather. RoHS Compliant	

Ver: 201113.NR.v1.0