

ACETAL CABLE ZIP TIE STRAPS TX-AT1850

18" ACETAL (DELRIN) TIE



General Specifications

457 mm 18.00 in 12.7 mm 0.50 in 1.32 mm 0.05 in Weather Resistant Acetal			
Black			
-40 °C to +85 °C (-40 °F to +185 °F)			
Mechanical Specifications			
250 lb			
Locking			
5.25 in			
5.25 in Compliant			
_			

Packaging

Package Quantity

50 per pack

Related Products

Part Number	Description	U of M
TX-AH25E	ACETAL LOCKING HEAD FOR DELRIN TIES	Pack of 25
TX-T3DY	BLUE TENSIONER TOOL FOR DELRIN TIES	Each

NOTE

Installation of this product should only be performed by trained, qualified and experienced personnel. Installation instructions for this product should be read thoroughly before installation is performed. The manufacturer and supplier of this product disclaims any liability or responsibility for the results of improper or unsafe installation practice.

When installed properly, this product meets the requirements for installation in High Risk PIM Zones. Static and dynamic testing was conducted per IEC 46/666 "Passive RF and Microwave Devices, Intermodulation Level Measurement", "Part 8: Measurement of passive intermodulation generated by objects exposed to RF radiation" and IEC 62037-1.

Rosenberger Site Solutions, LLC 102 Dupont Dr. Lake Charles, LA 70607 Version 051719