


LOW PIM CABLE MANAGEMENT BRACKET, SINGLE
D-SSAN5000



Dimensions

Height	57.15 mm 2.250 in
Length	457.20 mm 18.00 in
Width	419.10 mm 16.50 in
Weight	4.68 kg 10.33 lb

General Specifications

Cable Runs, quantity	Up to 14
Hole Quantity and Size	31 x 0.75" and 31 x 0.465"
Material Type	Steel
Finish	Hot Dip Galvanized

Mounting

Mounting Type	Round Member
Mounting Range	60.32 mm to 101.6 mm 2-3/8 in to 4 in OD
Torque	25 ft-lbs

Packaging



Package Quantity	1 Kit
------------------	-------

NOTE
Installation of this product should only be performed by trained, qualified and experienced personnel. Installation instructions for this product should be read thoroughly before installation is performed. The manufacturer and supplier of this product disclaims any liability or responsibility for the results of improper or unsafe installation practice.

When installed properly, this product meets the requirements for installation in High Risk PIM Zones. Static and dynamic testing was conducted per IEC 46/666 "Passive RF and Microwave Devices, Intermodulation Level Measurement", "Part 8: Measurement of passive intermodulation generated by objects exposed to RF radiation" and IEC 62037-1.



Material List

- 1) FRONT BRACKET WELDMENT - **QTY 1**
- 2) 3/8-16 X 10" GALVANIZED THREADED ROD - **QTY 2**
- 3) 3/8" THREADED ROD INSULATOR - **QTY 4**
- 4) 3/8 USS FLAT WASHER GALVANIZED - **QTY 4**
- 5) 3/8 LOCKWASHER GALVANIZED - **QTY 4**
- 6) 3/8-16 "NC" FINISHED HEX NUT GALVANIZED - **QTY 4**
- 7) REAR SADDLE - **QTY 1**



D-SSAN5000

Low PIM Cable Management Bracket, Single.



- 1) FRONT BRACKET WELDMENT - **QTY 1**
- 2) 3/8-16 X 10" GALVANIZED THREADED ROD - **QTY 2**
- 3) 3/8" THREADED ROD INSULATOR - **QTY 4**
- 4) 3/8 USS FLAT WASHER GALVANIZED - **QTY 4**
- 5) 3/8 LOCKWASHER GALVANIZED - **QTY 4**
- 6) 3/8-16 "NC" FINISHED HEX NUT GALVANIZED - **QTY 4**
- 7) REAR SADDLE - **QTY 1**

When installed properly, this product meets the requirements for installation in High Risk PIM Zones. Static and dynamic testing was conducted per IEC 46/666 "Passive RF and Microwave Devices, Intermodulation Level Measurement", "Part 8: Measurement of passive intermodulation generated by objects exposed to RF radiation" and IEC 62037-1.

Corporate Headquarters

Rosenberger Hochfrequenztechnik GmbH & Co. KG
P.O. Box 1260 D-84526 Tittmoning Germany

Rosenberger Site Solutions, LLC

102 Dupont Dr.
Lake Charles, LA 70607

Phone: (337)598-5250

Fax: (337) 598-5290

Web: www.Rosenberger Online.us

Version 051619

Page 1 of 1