


Technical Data Sheet

Rosenberger

FTTA Hybrid Jumper

LCC+2xAWG8-4F9μG657A2-LCC+2xAWG8

HJ-H300012XX



All dimensions are in mm; tolerances according to ISO 2768 m-H

Description

This 4 fiber FTTA hybrid jumper cable assembly connects remote radio heads (RRU) in telecommunication applications.

Side A consist of two 7 mm FO fan-out with an overmolded LC Compact connector as well as a 2 wire 8AWG shielded power connection fan-out.

The B Side of the corrugated hybrid jumper is designed to be connected to a FTTA box solution providing two 2,8 mm LC fan-out and a 2 wire 8 AWG interface for power connection.

Two ripcords underneath the copper tape provide an easy way to cut back the cable jacket on Side B.

The Assemblies can be used indoor and outdoor, are UV protected and flame retardant.

Available Variants

Type	Length (Ft)	weight (g)/(lb) / pce
HJ-H30001206	6	tbd
HJ-H30001209	9	tbd
HJ-H30001212	12	tbd
HJ-H30001215	15	tbd

Length (m)

L ≤ 10
10 < L ≤ 20

Tolerance (mm)

+100/- 50
+/- 200

Other length on request. Please mind derating!

Parts

Connector A	2 x LC Compact Duplex - overmolded, single mode
Connector B	2 x LC Compact Duplex - single mode
Cable	FRNC, UL Type 21285 black
Fiber marking	Identification ring on single fan-out
Ripcord	2x diametrically under corrugated copper-tape

Optical data

Cable	4 fibers
Fiber	9/125 μm single mode optical fiber according to ITU-T G.657A2
Cable attenuation	≤ 0.40 dB / km λ = 1310 nm ≤ 0.25 dB / km λ = 1550 nm

Connector A	LC Compact Duplex
Insertion loss	max. 0.30 dB
Return loss	typ. 55 dB (UPC)

Connector B	LC Compact Duplex
Insertion loss	max. 0.30 dB
Return loss	typ. 55 dB (UPC)

Electrical data

Power connectors	2 (black / red)
Conductor resistance	1.68 Ohm/1000ft@20°C
Operating voltage	up to 60 V DC / 48 V AC
Test voltage (rms 50Hz 1min)	1500 V
Derating according to	DIN EN60512-5-2: tbd

Mechanical data

Overall cable diameter, jacket	Ø16 +/- 0.3 mm
Divider Side A	~Ø36mm / ~180mm length
Fiber cable diameter	Ø7.0mm (Side A) Ø2.8mm (Side B)
Power cable diameter	AWG8 Ø5,4mm (Side A) AWG8 Ø5,4mm (Side B)
Shield conductor main cable	copper corrugation ½ Inch

Minimum bending radius

Cable	
Repeated	240 mm
Single	160 mm

FO Fanout (Ø2.8mm)	
Min. Bending Radius (Installation)	45 mm
Min. Bending Radius (In use)	30 mm

Max. tensile strength

Cable	500N
Fanout Side A (Ø7.0mm)	70N
Fanout- Side B (Ø2.8mm)	70N

