

RRU CABLE SUPPORT BRACKET KIT
D-RRU-4G-RUN

RRU CABLE SUPPORT BRACKET WITH PLASTIC STANDOFF ADAPTER KIT AND HOT DIPPED GALVANIZED THREADED ROD (4) RUNS. ACCOMODATES 2-3/8" OD TO 4" OD MEMBERS. SOLD ONE PER KIT



Dimensions

Height	50.80 mm 2.0 in
Length	368.3 mm 14.50 in
Width	304.8 mm 12.0 in
Weight	1.3607 kg 3.0 lb

General Specifications

Cable Runs, quantity	Up to 4
Hole Size	3/8 in
Hole, quantity	4
Material Type	Steel
Finish	Hot Dip Galvanized

Mounting

When installed in a High Risk PIM Zone, plastic cable strap or other approved non-metalic materials are required for mounting.

Mounting Type	Round Member
Mounting Range	60.32 mm to 101.6 mm 2-3/8 in to 4 in OD
Torque	25 ft-lbs

Packaging

Package Quantity	1 Kit
------------------	-------

When installed properly, this product meets the requirements for installation in High Risk PIM Zones. Static and dynamic testing was conducted per IEC 46/666 "Passive RF and Microwave Devices, Intermodulation Level Measurement", "Part 8: Measurement of passive intermodulation generated by objects exposed to RF radiation" and IEC 62037-1.

Material List

- Plastic Stand Off with 3/8" Threaded Hole
- Hose Clamp for 2-3/8" to 4" OD Round Member
- 12" Trapeze Angle
- 3/8" x 12" Hot Dipped Galvanized Threaded Rod
- 3/8" Hot Dipped Galvanized Nuts
- 3/8" Hot Dipped Galvanized Lock Washer

Corporate Headquarters

Rosenberger Hochfrequenztechnik GmbH & Co. KG
P.O. Box 1260 D-84526 Tittmoning Germany

Rosenberger Site Solutions, LLC

102 Dupont Dr.
Lake Charles, LA 70607

Phone: (337)598-5250

Fax: (337) 598-5290

Web: www.RosenbergerOnline.us

Version 031519

Page **2** of **2**