


Distributed By
Rosenberger
 Rosenberger Site Solutions, LLC
 visit www.RosenbergerOnline.us



ITEM #	DESCRIPTION	APPROX GALV WT
C10981201	2 3/8" O.D. X .134 X 1'-0	3.2#
C10981202	2 3/8" O.D. X .134 X 2'-0	6.4#
C10981203	2 3/8" O.D. X .134 X 3'-0	9.6#
C10981204	2 3/8" O.D. X .134 X 4'-0	12.8#
C10981205	2 3/8" O.D. X .134 X 5'-3	16.9#
C10981206	2 3/8" O.D. X .134 X 6'-0	19.3#
C10981207	2 3/8" O.D. X .134 X 7'-0	22.5#
C10981208	2 3/8" O.D. X .134 X 8'-6	27.3#
C10981209	2 3/8" O.D. X .134 X 9'-0	28.9#
C10981210	2 3/8" O.D. X .134 X 10'-6	33.7#
C10981211	2 3/8" O.D. X .134 X 11'-0	35.3#
C10981212	2 3/8" O.D. X .134 X 12'-0	38.5#
C10981213	2 3/8" O.D. X .134 X 13'-0	41.7#
C10981214	2 3/8" O.D. X .134 X 14'-0	44.9#
C10981215	2 3/8" O.D. X .134 X 15'-0	48.2#
C10981216	2 3/8" O.D. X .134 X 16'-0	51.4#
C10981217	2 3/8" O.D. X .134 X 17'-0	54.6#
C10981218	2 3/8" O.D. X .134 X 18'-0	57.8#
C10981219	2 3/8" O.D. X .134 X 19'-0	61.0#
C10981220	2 3/8" O.D. X .134 X 20'-0	64.2#
C10981221	2 3/8" O.D. X .134 X 21'-0	67.4#
C10981222	2 3/8" O.D. X .134 X 8'-0	25.7#
C10981223	2 3/8" O.D. X .134 X 5'-0	16.1#
C10981224	2 3/8" O.D. X .134 X 10'-0	32.1#
C10981225	2 3/8" O.D. X .134 X 9'-6	30.5#
C10981227	2 3/8" O.D. X .134 X 0'-6	1.6#
C10981228	2 3/8" O.D. X .134 X 4'-6	14.4#

FINISH: IN-LINE GALVANIZING (OR EQUAL)

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS INCLUDE FINISHES AND ARE IN INCHES				MATERIAL: PIPE 2 3/8 O.D. X SEE CHARTS ABOVE Fy = 45 ksi (OR EQUAL)								2 3/8" O.D. X .134" WALL PLAIN PIPE CUT LIST									
TOLERANCES: FRACTIONS ± 1/16" ANGLES ± 1/2 DEG. DECIMALS ± .010"				TOLERANCES DO NOT APPLY TO RAW MATERIAL																	
CONFIDENTIAL This document and the information contained herein is the confidential trade secret property of Sabre Communications Corporation ("Sabre") and must not be reproduced, copied or used, in whole or in part, for any purpose without the prior written consent of Sabre. © 2009 Sabre Communications Corporation. All rights reserved.												DATE		1/12/09		SIZE		DRAWING NO.		REV	
1		5/5/16		RWM		REVISED THE YIELD STRENGTH FROM 50 KSI TO 45 KSI AND REMOVED THE ASTM 500 REFERENCE.		B		C109812		1									
REV		DATE		DRW		CHK		DESCRIPTION		SCALE		PAGE									
										None		1 OF 1									